

WATERCOOLER



FEATURES

- No priming required
- Quick fill in & drain out
- Simple maintenance
- Visible water tank
- Ø200mm fan for the big radiator
- Easy operation
- Excellent design for ventilation
- Compact & light
- High heat exchanger
- Ideal for **MIG, TIG, PLASMA, SPOT, ETC, Welding Equipment**

TECHNICAL PARAMETER

MODEL	WRA-300S	WRC-500A
Input Voltage / Frequency	240V 50/60Hz	240V 50/60Hz
Motor	260W (0.9A/220V)	260W (0.9A/220V)
Rated Duty Cycle %	100	100
Max Pressure	3 Bar (30Mingh)	3 Bar (30Mingh)
Tank Capacity	9L	26L
Flow Rate	8.5L/min at 6mH	8.5L/min at 6mH
Operation Temperature	-20°C - 60°C	-20°C - 60°C
Heat Exchanger	280KJ/min	280KJ/min
Dimension mm	310 x 260 x 400	520 x 390 x 690
Gross Weight kg	16	33

**Technical information provided by the manufacturer*

SERVICE CENTER

K.L Office

No.13 & 15, Jalan BP5,
Bandar Bukit Puchong,
47120 Puchong, Selangor, Malaysia.
Tel : 03-8060 6131

J.B Office

No.3, Jalan Perdagangan 11,
Taman Universiti Industrial Park,
81300 Skudai, Johor, Malaysia.
Tel : 07-520 2093

DISTRIBUTED BY: