

DC INVERTER PLASMA CUTTER



DP-40



FEATURES

- The plasma cutting process is 1.8 times faster and more efficient compared to oxy acetylene cutting process.
- More cost saving for mild steel cuts below 12mm.
- Can cut multiple type of steel eg: steel, stainless steel, alloy steel, copper, aluminium.
- Ease of operation.
- Can be fitted with semi automatic line cutting machine for better improved cut quality.

TECHNICAL PARAMETER

MODEL		DP-40
Input Voltage / Frequency		1PH240 V 50/60Hz
Rated Input Power Capacity	KVA	4.8
Rated No-Load Voltage	V	230
Rated Output Voltage	V	96
Output Current range	A	20-40
Duty Cycle	%	60
Efficiency	%	85
Max. Cutting Thickness	mm	10
Power Factor		0.93
Compressed Air Pressure	KG/cm ²	4.0-5.0
Insulation Class		F
Protection Class		IP23
Dimension	MM	380 x 178 x 295
Gross Weight	KG	8

SERVICE CENTER

K.L Office

No.3, Jalan PTP 1/4,
Taman Perindustrian Tasik Perdana,
47120 Puchong, Selangor, Malaysia.
Tel : 03-8060 6131

J.B Office

No.3, Jalan Perdagangan 11,
Taman Universiti Industrial Park,
81300 Skudai, Johor, Malaysia.
Tel : 07-520 2093

DISTRIBUTED BY: