

DC INVERTER MIG WELDING MACHINE



FEATURES

- Low energy consumption and adaptability to input voltage fluctuation.
- Excellent arc start, low spatter level with high deposition.
- Inverter IGBT technology, reliable and efficient.
- Excellent weld, less thermal deformation especially for thin plate welding.
- Suitable for all- round welding of carbon steel, low-alloy steel and tool steel etc.

TECHINCAL PARAMETER

MODEL		PM 2000
Input Voltage / Frequency		1PH 240V 50/60Hz
Rated Input Capacity	KVA	7.4
Rated No-Load Voltage	V	50
Output Voltage Range	V	15.5-24
Output Current Range	A	30-200
Rated Duty Cycle	%	60
Efficiency	%	85
Power Factor		0.76
Insulation Class		F
Protection Class		IP23
Dimension	MM	510 x 270 x 500
Gross Weight	KG	31

SERVICE CENTER

TTMC WELDING SUPPLIES SDN BHD

No.3, Jalan PTP 1/4,
Taman Perindustrian Tasik Perdana,
47120 Puchong, Selangor, Malaysia.
Tel : 03-8060 6131 Fax : 03-8060 6639
Email: derrick@ttmcwelding.com

TTMC SDN BHD

No.3, Jalan Perdagangan 11,
Taman Universiti Industrial Park,
81300 Skudai, Johor, Malaysia.
Tel : 07-520 2093 Fax : 07-520 2016
Email: ttmclim@ttmcwelding.com

Branch

No.21, Jalan Mutiara Emas 7/7,
Taman Mount Austin,
81100 Johor Bahru, Johor, Malaysia.